



Locomotive Release from Shop Form

To be completed on every engine released from the Shop

I have reviewed the work packet for locomotive 8546 on this date 3-15-11 and take no exception to applicable laws, rules and or MMA standards, policies and standards.

*NO LOAD -*

*Bad Slip Ring com 1*

*Replaced Com with R.T.O.*

*NEW Brushes*



UNIT \_\_\_\_\_

DATE \_\_\_\_\_

## Service Operations

### THROTTLE 8 INBOUND LOAD TESTS

Eng RPM (900)	EMD	_____	Lube Oil Pres	_____
Eng RPM (1050)	GE	_____	Water Temp	_____
Horsepower		_____	Overspeed Setting	_____
Volts (5.3)	B-23	_____	RACK SETTING	_____
Volts (7)	C-30	_____		
Volts (720)	B-39	_____		

### THROTTLE #1 STALL TEST

OP Mode	(PWR)	_____	
AMPS	(300)	_____	
MGA	(1220)	_____	NOT APPLICABLE TO B-23 AND C-30
Charging Rate	(70v)	_____	

### TL 24T

Throttle 1	(1V)	_____
Throttle 2		_____
Throttle 3		_____
Throttle 4		_____
Throttle 5		_____
Throttle 6		_____
Throttle 7		_____
Throttle 8	(72V)	_____



B-23, B-39, C-30, GP-7 UNSCHEDULED

UNIT:

ITEM	<i>Running Mechanical</i> MECHANICAL	WORKED BY:
	INSPECT ENGINE OVERHEAD (WITH ENGINE AT IDLE):	
	PROPER LUBRICATION? FUEL LEAKS? CAM ROLLER ROTATION? ETC.	
	INSPECT FUEL SYSTEM HOSES AND PIPES FOR LEAKS	
	INSPECT COOLING SYSTEM:	
	A: CHECK HOSES AND PIPES FOR LEAKS	
	VISUALLY INSPECT AIR COMPRESSOR FOR WATER, AIR OR OIL LEAKS	
	TEST AIR BRAKE EQUIPMENT PER RULE 212	
	PERFORM PENALTY BRAKE TEST	
	CHECK FLUID LEVELS BEFORE LOADING:	
	A: ENGINE OIL	
	B: COOLING WATER	
	C: AIR COMPRESSOR OIL	
	TEST OPERATION OF THE FOLLOWING DEVICES:	
	A. BELL	
	B. SANDERS (FORWARD, REVERSE, EMERGENCY)	
	C. RADIATOR SHUTTERS	
	INSPECT AIR COMPRESSOR GOVERNOR SETTING. 135 TO 145 PSI	
	INSPECT SAFETY POP. 155 PSI	



# Service Operations

## THROTTLE 8 OUTBOUND LOAD TESTS

UNIT \_\_\_\_\_

DATE \_\_\_\_\_

Eng RPM (900)	EMD	_____	Lube Oil Pres	_____
Eng RPM (1050)	GE	_____	Water Temp	_____
Horsepower		<u>3760</u>	Overspeed Setting	_____
Volts (5.3)	B-23	_____	RACK SETTING	_____
Volts (7)	C-30	_____		
Volts (720)	B-39	<u>73.9</u>		

### THROTTLE #1 STALL TEST

OP Mode	(PWR)	_____	
AMPS	(300)	_____	
MGA	(1220)	_____	NOT APPLICABLE TO B-23 AND C-30
Charging Rate	(70v)	_____	

### TL 24T

Throttle 1	(1V)	_____
Throttle 2		_____
Throttle 3		_____
Throttle 4		_____
Throttle 5		_____
Throttle 6		_____
Throttle 7		_____
Throttle 8	(72V)	_____

C.C.P.'s Check Base For Pressure on out Board

73.9 V = 3760 HP

3802 A

710 V

Unit: 8546

Date: 3-15-11

### DEFECTS FOUND DURING INSPECTION

DEFECT <u>NO LOAD Slip Ring Com on</u> <u>MAIN BRN Grounded / DAMAGED.</u>	INSPECTED BY: <u>J. HORTON</u>
REPAIR <u>Replaced com w/ RTO.</u> <u>NEW Brushes, STORARD Room - OIL</u>	CORRECTED BY: <u>JH/JB</u>

DEFECT _____	INSPECTED BY: _____
REPAIR _____	CORRECTED BY: _____

DEFECT _____	INSPECTED BY: _____
REPAIR _____	CORRECTED BY: _____

DEFECT _____	INSPECTED BY: _____
REPAIR _____	CORRECTED BY: _____

DEFECT _____	INSPECTED BY: _____
REPAIR _____	CORRECTED BY: _____

Unit: \_\_\_\_\_

Date: \_\_\_\_\_

## DEFECTS FOUND DURING INSPECTION

DEFECT _____ _____ _____	INSPECTED BY: _____ _____
REPAIR _____ _____ _____	CORRECTED BY: _____ _____

DEFECT _____ _____ _____	INSPECTED BY: _____ _____
REPAIR _____ _____ _____	CORRECTED BY: _____ _____

DEFECT _____ _____ _____	INSPECTED BY: _____ _____
REPAIR _____ _____ _____	CORRECTED BY: _____ _____

DEFECT _____ _____ _____	INSPECTED BY: _____ _____
REPAIR _____ _____ _____	CORRECTED BY: _____ _____

DEFECT _____ _____ _____	INSPECTED BY: _____ _____
REPAIR _____ _____ _____	CORRECTED BY: _____ _____







